

Industrial Routers LAN ROUTER

XR5i v2E Series

B+B SMARTWORX

Powered by

ADVANTECH



PRODUCT FEATURES

- Modular design to fit application requirements
- Provided secure connection between two networks
- SNMP protocol for remote management
- 2x ETH, Optional WiFi
- VPN support

The XR5i v2E industrial router secures connections between two local networks (LAN) via two Ethernet interfaces 10/100. WiFi model is available.

Configuration is password protected, via web interface. The router supports creation of VPN tunnels using IPsec, OpenVPN and L2TP to ensure safe communication. Web interface provides detail statistics about router activities.

SELECTED APPLICATIONS

Transportation and security
IT and communication
Self-service terminals
Energy and power industry
Metrology, alarm and warning systems

ORDERING INFORMATION

Note: Check with your local distributor for availability and options. Contact Advantech B+B SmartWorx distributors.

Europe, Middle East, Africa, Asia, South America, Latin America.

BB - XR 2 L000 XXX

Accessories

0	No Accessories
1	Accessories with EU power supply
2	Accessories with UK power supply
3	Accessories with Australia power supply
4	Accessories with US power supply

Enclosure

1	Plastic enclosure
2	Metal enclosure

0	No WiFi
7	WiFi

ACCESSORIES

ORDER CODE	DESCRIPTION	INCLUDED IN PACKAGE	INCLUDED IN SET PACKAGE	SOLD SEPARATELY
BB-SBD40	Metal DIN holder for Metal versions of routers v2	✓	✓	✓
BB-CPD2-G	Plastic DIN holder for Plastic versions of routers v2	✓	✓	✓
BB-AW-A24G-M5SRP	Antenna WiFi stick 5dB, SMA-RP connector		✓	✓
BB-KD-ETH	Ethernet cross cable 1,5m		✓	✓
BB-CON-WR2	2-pin Terminal block for Power Supply	✓		✓
BB-RPS-v2-WR2-EU	Power supply with WR connector (2 pins) - 12V/1A - EU plug		✓	✓
BB-RPS-v2-WR2-US	Power supply with WR connector (2 pins) - 12V/1A - US plug		✓	✓
BB-RPS-v2-WR2-UK	Power supply with WR connector (2 pins) - 12V/1A - UK plug		✓	✓
BB-RPS-v2-WR2-AUS	Power supply with WR connector (2 pins) - 12V/1A - AUS plug		✓	✓
BB-KN-WR2-3	Power supply cable 2-wire, 3m		✓	✓
Quick Start Guide		✓	✓	

Industrial Routers LAN ROUTER

XR5i v2E Series



SPECIFICATIONS

FIXED INTERFACES

2x Ethernet 10/100 Mbps, independent or bridged

POWER

Source 9 - 36 VDC
Idle - 1.6 W
Consumption WiFi Com. to 1.9 W
Full Com. to 2.5 W

MECHANICAL

Dimension Plastic version 51 x 87 x 116mm
Dimension Metallic version 42 x 87 x 113mm
Protection IP30

ENVIRONMENTAL

Operating Temperature -40 to +75°C
Storage Temperature -40° to +85°C
Humidity Operating - 0 to 95% relative humidity non condensing
Storage - 0 to 95% relative humidity non condensing

WiFi ^{optional}

Antenna connector R-SMA – 50 Ohms
Supported WiFi band 2.4 GHz
Standards 802.11b, 802.11g, 802.11n
2.4 GHz supported channels 1, 2, 3, 4, 5, 6, 7, 8, 9, 10, 11, 12, 13
RX Sensitivity 11b, 11 Mbps: typ. -85 dBm
11g, 54 Mbps: typ. -70 dBm
(HT20) 11n, MCS7: typ. -66 dBm
(HT40) 11n, MCS7: typ. -62 dBm
11b, 11 Mbps: min. 18, typ. 19, max. 20 dBm
11g, 54 Mbps: min. 14.5, typ. 16, max. 17.5 dBm
802.11n (HT20): min. 13.5, typ. 15, max. 16.5 dBm
802.11n (HT40): min. 13.5, typ. 15, max. 16.5 dBm
TX Output Power
Type of device Access point, station

CPU & MEMORY

CPU 32b ARM microprocessor, 0.25 DMIPS per MHz
Flash memory 16 MB DDR SDRAM
RAM 64 MB
M-RAM 128 kB

SOFTWARE FEATURES

Linux based, possibility to program your own application
NTP client, NTP Server – time synchronization
M-RAM memory inside – router statistic's saving into memory
NETWORKING
DHCP – automatic IP addressing in LAN network
NAT/PAT – IP address and ports translation between inside/outside network
VRRP – virtual backup router function
DynDNS client – access to the router with a dynamic IP address
PPPoE Bridge – PPP frames encapsulation inside ETH frames

VPN TUNNELING

IPsec, OpenVPN, L2TP – secure encrypted tunnels

CONFIGURATION AND DIAGNOSTIC

HTTP server – configuration via web server
Telnet – configuration and access to the file system
SNMP – router diagnostics, communication with I/O and M-Bus
Remote router group configuration change, switching among configuration profiles
SSH – encrypted configuration and access to the file system

STANDARDS/REGULATION

EMC ETSI EN 301 489-1 V2.1.1, ETSI EN 301 489-17 V3.1.1
Safety EN 60950-1:2006 + A11:2009 + A1:2010 + A12:2011 + A2:2013 + AC:2011

R-SEENET™

Router Management Software consisting of two parts:

R-SeeNet Server application can be programmed to automatically send SNMP queries (Simple Network Management Protocol) to each router defined in the network. The application retrieves status information from the routers and records it in the SQL database.

R-SeeNet PHP is a web-based application that accesses the SQL database and provides the network administrator detailed information on individual routers and network health.

SMARTWORX HUB™

SmartWorx HUB takes management of your devices to new levels of flexibility and efficiency. Giving you a complete view of your installed device population, SmartWorx Hub delivers invaluable configuration, diagnostic and management facilities directly to your desktop, wherever you are.

Manage a single device or your entire device population at the same time. Whether you need to modify configuration parameters, download or upgrade installed firmware and applications or view detailed information regarding network statistics, you can do it all from any location.

B+B SMARTWORX

Powered by

orders@advantech-bb.com
support@advantech-bb.com

Corporate Headquarters: 707 Dayton Road, PO Box 1040 Ottawa, IL 61350 USA 815-433-5100 Fax 433-5104
European Office: Westlink Commercial Park, Oranmore Co. Galway Ireland +353 91 792444 Fax +353 91 792445